

Oasis Series



THREE FUNCTIONS ELECTRIC BED

Registration code: SKD-C



SAIKANG/Medical

Healthier your life

Y6W

FEATURES AND HIGHLIGHTS

Technical parameters

External size (LxW):	2130x1015 mm
Mattress platform:	1925x880 mm
Safe working load:	250 kg
Height adjustment:	365-805 mm
Back-rest adjustment:	0-75° (±10°)
Knee-rest adjustment:	0-35° (±10°)
Bed Extension:	200mm
Auto-regression:	100+60mm
Voltage and frequency:	100-240 V · 50/60 Hz
 Plug as required (hospital grade) 	

Technical configuration

☑ Linear Motor	3pcs
☑ 5" Hardshell Castors	4pcs
☑ Foldable Side Rail with ProErgo-Handle™	1set
☑ ABS Oasis Bed Ends with Safe Lock	1set
☑ PP Bed Platform, Removable & Washable	9pcs
☑ Ø100mm Wall Bumper Wheel	4pcs
☑ IV Pole	1set
☑ IV Pole Prevision	4pcs
☑ Drainage Hook	2pcs
✓ ABS Mattress Stopper	2pcs
☑ Hand Controller	1pc

Optional

Optionat
☐ Manual CPR
☐ Electric CPR
☐ Bed Extension 20cm
☐ Back-up Battery
☐ Nurse Control Panel
☐ Emergency Stop Button
☐ Directional Wheels Function
☐ Monkey Pole
☐ Balkan frame






















Double Regression Function

Auto-Regression 10+6 cm
When repositioning the backrest and
thigh rest, the Y8y makes the back plate
retreat 10cm and the thigh plate retreats
6cm so to minimises the pressure and
shear forces in the patient's pelvic region.
This results in a significant reduction in
the development of pressure ulcers.



Electric Motor

Linear motor, with UL/ROHS/EN standard. Noise under 50 dB, with lifetime 20,000 times movement.



Plastic

Environmental plastic can be sterilized in 100°C, tensile upto 30MPa Virgin ABS material.



Steels | Painting

Baosteel from Fortune Global 500 $11\,\mathsf{Process}\,\mathsf{epoxy}\,\mathsf{painting},\mathsf{ASTM}$ testing anti-baterial, paint thickness 0.12mm, brightness 60°, paint can resist 50kg impact.



Welding | Chassis

Panasonic Robotic ensure, 360° full smooth wedlding. Solid bed base made of 3.0mm stamped rotating plate.



Head & Foot Board

Patented design Detachable head & foot board, using the eccentric locking structure, one step quick removable.



Safety Guardrail

L-shaped foldable guardrail(Patent), bended tube, solid installing, 0 shaking, anti-pinch, protect patient's safety.



Castors

5" hardshell casters TPR tire no worn out after running 30KM, save anti-winding hard shell, united forming without bolts. Pass Dynamic test: Bearing 120kg run 30KM and pass obstacles 500 time.



Joint-Free Technology

Removable plastic covers formed from 9 removable blow moulded lamella to minimise the slots where unwanted infections may hide.



Bed Extension

Extended bed platform up to 20CM, comfortable for the tallest of patients (option).



Mattress

Mattress Holder.



Wall Bumper Wheel

Horizontal corner bumpers at the outermost periphery of the bed to protect the bed and wall.



IV Pole

Full stainless steel IV pole, bearing 15 kg.



Drainage Hooks

Mobile plastic drainage hooks.

















Design

Research

Manufacturing

Maintenance

Service



USA

Saikang Medical Technology, Inc. 17800 Castleton St Ste 180, City of Industry, 91748, California. Tel.: +1 949648 2776

United Kingdom

UK Healthward International Ltd.Dept. 111, 196 High Road Wood
Green, N22 8HH, London.
Tel.: +44 2032399738

Russia

Saikang Medical Russia LLC Truda 174, 454080 Chelyabinsk. Tel.: +7 (351) 214 5566 / 8811 / 1516

East Africa

Saikang Medical Solutions Ltd. Viraj Complex Unit 3, Mombasa Road, P.O. Box 14262-00800, Nairobi. Kenya. Tel.: +254733704690

Middle East

Saikang Medical Supplies LLC X22-S03 England Cluster, International City, Dubai. United Arab Emirates. Tel.: +20 128 8962497

SAIKANG Medical







www.saikangmedical.com







Jiangsu Saikang Medical Equipment Co., Ltd. STOCK CODE: 870098

Company video

General catalogue